



# Danfoss' Solution to liquid cooling challenges

One partner, complete solution



**Danfoss Hansen® FD83 Series**  
An industry standard, our stainless steel FD83 has been supporting data center liquid cooling reliably for decades.



**Danfoss Hansen® Universal Quick Disconnect Blind-Mate (UQDB)**  
Offers a self-alignment feature to help connect in location with limited access or visibility and guarantees 100% helium-leak testing.



**Danfoss Hansen® OCP ORV3 Blind-Mate Quick Connector**  
Its self-centering design offers misalignment compensation, ensuring simple and secure connection between the blade and rack manifold.



**EverCool™ GH001 Hose & EZ Clip Fittings**  
Compatible with main refrigerant on the market with low permeation assembly – ideal solution for the application.



**90° Swivel Adapter**  
Specifically developed for liquid cooling hose assembly connection.



**Boston by Danfoss™ EHW194 EPDM-P Hose**  
Engineered for durability and ease of use, EHW194 UL94V-0 hoses feature industry-leading safety ratings, superior kink resistance and long-lasting performance.



**Danfoss Hansen® Universal Quick Disconnect Coupling**  
Complying to OCP standards, the UQD provides high flow and reduced pressure drop to fit inner-rack application needs.



**Socketless Hose and Fitting**  
Engineered to be flexible, abrasion resistance, perfect for low pressure and very easy to assembly, no tools needed.